

CENTER 375 Precision RTD Thermometer



• FEATURES

- Precison Platinum Temperature sensor
- High Accuracy with 0.01°C resolution
- Automatic Locked Push-Pull Connector for easy connection
- Large Back Light LCD
- Dual Display
- MAX/MIN Function
- °C, °F Scale selectable
- Data Hold Function
- Relative Function
- 100 Manual Recording Data Memory Include on Meter Readout Function
- Auto Power Off
- User Offset Adjustable
- Tilt Stand



Within PT100 Probe (TP-R03 x 1pc.)

SPECIFICATIONS

Measurement Range	-100 ~ 400°C; -148 ~ 752°F
Measurement Accuracy	±0.05%rdg ±0.1°C
Resolution	0.01°C; 0.02°F
Sampling Rate	2 times/sec.
Battery	9V Battery
Dimensions	185(L) x 65(W) x 36(H) (Meter only)
Weight	Approx. 360g.
Sensor Type	Platinum temperature-measurement resistor (PT100/4 line type)

CENTER 376 Precision RTD Thermometer

(Datalogger, PC Interface)

• FEATURES

- Precison Platinum Temperature sensor
- High Accuracy with 0.01°C resolution
- Automatic Locked Push-Pull Connector for easy connection
- Large Back Light LCD
- Dual Display
- MAX/MIN Function
- °C, °F Scale selectable
- Data Hold Function
- Relative Function
- 16,000 Records Datalogger.
- Record Temperature, Time and Date of measurement
- With Windows Software
- PC Interface
- Auto Power Off
- User Offset Adjustable
- Tilt Stand

STANDARD ACCESSORIES

Precision PT100 Probe, 9V Battery, Instruction Manual, Carrying case, Software376 (376), USB Cable(376), RS-232 Cable (Option), AC Adapter(Option)



Within PT100 Probe (TP-R04 x 1pc.)